



NEOLITH<sup>®</sup>  
Polished Finish Manual

# NEOLITH<sup>®</sup> Polished Finish Manual

## INDEX

---

1. Technical Features	3
2. Neolith Polished Applications	3
3. Cleaning and Maintenance	3
4. Handling of Polished slabs	4
5. Mechanical Fabrication of Polished Countertops	5
6. Bridge Saw, Waterjet y CNC	5
7. Waterjet Warnings	5
8. Polished Edges	5
9. Hand Fabrication Instructions of Polished Countertops	6
10. Handling of Slabs	6

### GUIDE TO REPAIR SURFACE SCRATCHES ON NEOLITH POLISHED SLABS

1. Required Materials	7
2. Instructions	7

TECHNICAL DATA	9
----------------	---

## 1. Technical Features

---

FORMAT	3.200 x 1.500 mm - 125" X 60"		3.200 x 1.600 mm - 126" X 64"	
THICKNESS	6 mm - 1/4"	12 mm - 1/2"	12 mm - 1/2"	20 mm / 3/4"
FULL SLAB WEIGHT (Kg)	90 Kgs	150 Kgs	158 Kgs	261 Kgs

## 2. Neolith Polished Applications

---

- Countertops.
- Interior and Exterior cladding.
- Interior flooring with low intensity pedestrian traffic and no outdoors connection.

## 3. Cleaning and Maintenance

---

Cleaning should be limited to immediately rinse the spills off the surface and dry with an absorbent cloth. For daily cleaning use only a damp cloth with water and soap.

For embedded stains, pour warm water on the stain then wait till it "loosens" and finally rinse or remove with a clean cloth.

Avoid using pads, rough sponges and steel wool. TheSize recommends using a blue pad: made with soft fibers, suitable for cleaning of glass, kitchen appliance and nonstick frying pans.

Do not use caustic soda or products with a pH greater than 11. If you use bleach, rinse with plenty of water and never leave it in permanent contact with the Neolith polished surface. Avoid cleaning the surface with abrasive cleaners such as Cif Cream (Soft Scrub Cream Cleansers).

Use pads, cloths, napkins and glass coasters to place cooking pots or other kitchen hardware on the surface.

Never cut food directly on the counter, use a cutting or chopping board.

Do not pull or drag kitchenware, pans and appliances on the counter.



## 4. Handling of Polished Slabs

---

The Neolith slabs must be loaded, unloaded and transported by a forklift, crane or other lifting device. In all cases, handling and transport of the slabs must be balanced taking into account its center of gravity.

Always pay attention to the movement and handling of the slabs to prevent chipping or breakage.

To lift and move individual slabs, TheSize recommends the use the following type of clamp.



Image 1: Clamp



Image 2: Neolith slab handling with Clamp

**Be sure to cover all metal surfaces that may come into contact with the polished slab with adhesive foam tape.**

This clamp is available through TheSize. Contact TheSize for details.

- Before picking up the slabs with the clamp, remove the protective plastic from the slabs.
- It is not recommended to take more than 2 slabs at once with the clamp.

In case of not having this type of clamp, use a 2 cm plank of approximately 3 m x 20 cm. Place the plank on the back of the slab.



Image 3: Plank in the backside of the slab



Image 4: Handling with Clamp

- 1) Put the clamp on the slab and plank together.
- 2) Attach the clamp and lift the slab with caution.
- 3) Avoid sudden changes of direction.

**To avoid damage, it is recommended to store the polished slabs indoors.**

## 5. Mechanical Fabrication of Polished Countertops

---

TheSize strongly recommends wet cutting to fabricate Neolith Polished countertops.

## 6. Bridge Saw, Waterjet and CNC

---

Follow the same cutting instructions as for Neolith Satin or Silk slabs.

## 7. Waterjet Warning

---

When starting the cut with the waterjet, ensure that the initial perforation is far enough away from the work area due to the risk of chipping.

## 8. Polished Edges

---

The edge polishing of a Neolith Polished slab should be done with water. This factor ensures a higher level of brightness and reduces the chipping possibilities in the edges.

## 9. Hand Fabrication Instructions of Polished Countertops

---

For the manual cutting of a hole it is recommended to use the disk for dry cutting, available through TheSize.

When dry cutting, please note that there will be more chances of chipping during the process, therefore keep this in mind when marking and making the hole.

After cutting it is recommended grinding the edge of the hole to the desired size, using our recommended grinding discs and cups.

Drilling must be done by using water as coolant.

More information related to the Neolith slabs handling and fabricating recommendations, can be found in our **Countertop Technical Guide**, available in the download area of [www.neolith.com](http://www.neolith.com).

## 10. Handling of Polished Slabs

---

Due to its composition, the polished slabs are more sensitive to bending. **Make sure never to bend the slab by stretching the polished side.**

To avoid unexpected bendings during transportation, it is recommended to fasten the countertop with an aluminium bar and grips.

# GUIDE TO REPAIR SURFACE SCRATCHES ON NEOLITH POLISHED SLABS

## 1. Required Materials

---

- GlassRenu® Professional Grade System
- Electric Variable Speed Grinder
- Dust Mask
- Lint Free Cloth
- Water
- Spray Bottle
- Goggles

Before starting the scratch removal process on the polished surface of the slab, the depth of the scratches should be inspected. If scratches can be felt with a fingernail, it means that you will need to start with a BLACK RenuDisk that can be found in the GlassRenu System. If the scratch cannot be felt with a fingernail, the scratch can be removed with the polishing compound and felt disk supplied in the system.

## 2. Instructions

---

PLEASE TAKE THE TIME TO READ THE INCLUDED INSTRUCTIONS THAT CAN BE FOUND WITHIN THE GLASSRENU PROFESSIONAL GRADE SYSTEM PRIOR TO ATTEMPTING A REPAIR.\*

1. Mix the complete pouch of dry polishing compound supplied in the system with 475ml of clean water in the spray bottle.
2. Clean the surface of the slab thoroughly to remove all traces of dirt and grease.
3. If the scratch can be felt with a fingernail, you will need to grind the surface of the slab using a new Black RenuDisk to remove the scratch. With the Black RenuDisk attached to the included backing pad, set your variable speed grinder to 1800 RPM and move the pad up and down, left and right over the scratched area. Note that this grinding is done DRY and should only take a few passes to remove the scratch. This step should only take a few minutes to complete. If the scratch cannot be felt with a fingernail skip to step 5.

4. Once the scratches are no longer visible on the surface of the slab, remove the Black RenuDisk from the backing pad and replace it with a new Grey or “Pre-Polish” RenuDisk. Use this disk in the same manner, and at the same speed as the Black RenuDisk. Make at least 3 full passes over the repair area to get the slab ready for polishing. You will know you are done pre-polishing once the surface of the slab looks uniformly hazy. This process should take only 2-3 min per square foot of repaired area.
5. Remove the Grey RenuDisk from the grinder and attach the Felt Polishing Pad. Mist the polishing solution (from Step 1) onto the surface of the polishing felt insuring the surface is damp to the touch and not dripping (4 to 5 sprays). Begin polishing the repair area on the surface of the slab. The slab will polish quickly; just insure that the surface is clear from all observable angles.
6. Clean the polish off the slab and carefully inspect the repaired area. Keep polishing until obtaining a satisfactory result.

\* **NOTE:** IF YOU HAVE SPECIFIC QUESTIONS OR REQUIRE FURTHER INFORMATION CONTACT EITHER YOUR NEOLITH DISTRIBUTOR OR GLASSRENU DIRECTLY ([www.glassrenu.com](http://www.glassrenu.com)).



# NEOLITH<sup>®</sup>

---



## **POLISHED**

### **TECHNICAL DATA**

**JUNE 2018**

# FORMATS AND THICKNESS

— NEOLITH POLISHED



**6 mm - 1 /4"**



**12 mm - 1/2"**



**20 mm - 3/4"**




# COLOR RANGE

NEOLITH POLISHED



Artic white




Bombón



Luna




Nero




Blanco Carrara




Calacatta




Calacatta Gold




Estuario E01/E01R




Estuario E05/E05R



Nero Marquina



Pulpis



Onyx translucent

# TECHNICAL DATA

NEOLITH POLISHED

## SPECIFICATIONS

Format (mm)	3200 x 1500		3200 x 1600	
Weight slab (Kg)	6 mm	90 Kgs	12mm	158 Kgs
	12mm	150 Kgs	20mm	261 Kgs

Besides the formats described above, slabs can be cut to the following standard sizes:

Length (mm)	Width (mm)
1500	1500
1500	750
750	750

For special projects, slabs can be cut to size.

PROPERTIES	TEST METHOD	VALUE		
Water absorption (%)	ISO 10545-3	≤ 0,1		
Coefficient of linear expansion (10 <sup>-6</sup> · °C <sup>-1</sup> )	ISO 10545-8	5,2 – 6,3 10 <sup>-6</sup> ·oC <sup>-1</sup>		
Thermal Shock Resistance	ISO 10545-9	Pass, no defects.		
Moisture Expansion (mm/m)	ISO 10545-10	≤ 0,1		
Resistance to Dry Heat	ISO 19712	Pass, no defects		
Hardness (Mohs)	UNE 67-101	> 4		
		<b>6+</b>	<b>12mm</b>	<b>20mm</b>
Breaking Strength (N) (Average)	ISO-10545-4	1807	5451	
Modulus of Rupture (N/mm2) (Average)	ISO-10545-4	57	51	55

## Recommended Applications:

- Countertops. (12mm, 20mm)
- Interior and exterior cladding.
- Floor coverings in areas that are walked on essentially with soft soled footwear or bare feet without scratching dirt. (Areas without direct access from the outside)



Produced by:

**Thesize**<sup>®</sup>  
SURFACES

P.I. Camí Fondo, Supoi 8. C/ Dels Ibers, 31  
Almassora (Spain)

+34 964 652 233

[info@thesize.es](mailto:info@thesize.es)

[www.neolith.com](http://www.neolith.com)

Marketed by:

**NEOLITH**<sup>®</sup>  
DISTRIBUTION